

**Solvent based Charcoal Stain****Type of Product**

Solvent based diluted Charcoal Stain

**Main properties**

Good Grain filling, Good Drying

**Physical-chemical characteristics**

<b>Specific Gravity</b>	0.84 ± 0.03
<b>Viscosity FCB4</b>	10 ± 2
<b>Color</b>	Charcoal

**Application systems**

The product can be applied by the followings systems:  
Brush, Spray Application.

**Usage field**

Recommended fields of employment are:  
Suitable for interior carpentry, doors, windows, furniture, gardening, beams ...

**Storing and packaging.**

To verify technical measures of product storage, conditions, and possible incompatibilities, adhere to instructions described in section 7.2 of the Material Safety Data Sheet.  
The product must be stored in accordance with current legislation. Default terms are to keep the containers in a dry, cool, well-ventilated area and away from sources of ignition and heat. Containers should be kept perfectly closed and leak-proof.

- Available sizes: 100 ML, 1 Lit

**Remarks**

This technical data sheet is solely for information purposes! The information provided complies with the latest standards and is based on years of experience in the manufacture of our products. However, the information contained herein is not binding. Please follow the guidelines in the corresponding Safety Data Sheet for the product and warnings on the labels. We reserve the right to add or remove information and to make changes to the information in the Technical Data Sheet at any time without prior notice.